


The CP-2402E is a XY Control Panel with 29 illuminated pushbuttons and two display windows used for source and destination scroll lists. The CP-2402E is available as a remote control panel and can be used on any Evertz family of small routers, such as Topaz, EQT and Xenon.

The CP-2402E is programmable and therefore the operation of the panel is entirely dependent upon its configuration. It can be configured in a number of different ways including XY (using scroll lists) and multi-destination. Each button can be individually configured for any combination of source, destination, breakaway or control functions.

The physical button layout of the CP-2402E guides its configuration but does not restrict it. For example, the left hand block of 24 buttons can be programmed as sources. A number of these buttons can also be used for other functions such as level selection, lock etc. The two display windows can be used to show the current selected destination and the selected source. The two buttons located next to the display windows can be used to scroll up or down through the source or destination list. The take button confirms the selection.

### ►Features & Benefits

- 1RU panel with internal power supply
- 15mm LED illuminated square buttons suitable for film legends
- Buttons with high quality positive action
- Fully programmable to operate in a number of modes
- Buttons can be programmed for breakaways, level selection etc.
- Optional lock button protects against accidental or unauthorized selections
- Camera joystick override on any eight inputs with momentary or latching action
- Suitable for applications with a matrix size of up to 32x32
- Supports Qlink for legacy router control. Directly connects to most Evertz routers for simple router control. Contact factory to ensure support.
- Supports Ethernet for connection to MAGNUM Router Control System



### ►Specifications

<p><b>Control:</b> Joystick: 8 Parallel contact closures, TTL levels (GPI) D9 male</p> <p><b>Qlink:</b> 75Ω coaxial connection for direct connection to routers BNC, "T" adapter and termination required</p> <p><b>Ethernet:</b> Standard Ethernet interface for connection to MAGNUM Router Control system. RJ45. (please note routers DO NOT support Ethernet panels directly)</p>	<p><b>Electrical:</b> Voltage: Auto ranging, 100 ⇔ 240 VAC, 50/60 Hz or 12 VDC, 3A</p> <p>Power: 40W Fuse Rating: 250V, 1A, time delay</p> <p><b>Physical</b> Height: 1.75" (45 mm) 1 RU standard rack height Width: 19" (483 mm) 19" Rack Mount Depth: 3.5" (89 mm) not including connectors Weight: 3 lbs. (1.36 kg) Operating Temp: 0-40°C</p>	<p><b>Desk Top Mounting (Optional):</b> Panel Depth: 1.4" (35mm) Chassis Depth: 3.5" (89mm) Distance from Panel to Chassis: 40" (1m)</p> <p><b>Compliance:</b> Safety: ETL Listed, complies with EU safety directives EMI/RFI: Complies with FCC Part 15 Class A regulations Complies with EU EMC directive</p>
---	---	---

### ►Ordering Information

<b>CP-2402E</b>	Remote Control Panel, 1RU 29 buttons
-----------------	--------------------------------------

**Ordering Options:**  
CP-1000E-DMK Desk Mount Kit for CP-1000E